

StarPack - High precision GNSS positions, heading and time from a single platform



The StarPack is Fugro's answer to increasing market demand for precise, redundant GNSS positioning solutions, including extensive QC and accurate time, from a single, easy to use platform.

StarPack platform

The StarPack unit consists of a survey grade GNSS combined L-band receiver and powerful processor, running Linux multitasking operating system. The receiver is capable of tracking all current satellites (GPS, GLONASS) and is Galileo ready. StarPack can be extended with a second GNSS card (in the same unit), to provide accurate, GNSS derived heading. In addition to GNSS observations, the second card provides also L-band functionality, creating an independent source of corrections for backup.

The combination of receiver and processor provides robust multiple simultaneous precise position calculations and extensive QC. For maximum system reliability, the internal software is embedded on a flash memory. System can be controlled and configured via the front panel, web interface or a serial port.

The StarPack is equipped with four serial ports on the rear panel and LAN interface to provide a multitude of outputs to the user and to read multiple correction sources (in addition to those from the integrated receiver(s)). Raw GNSS data and corrections are continuously logged internally and can be exported to RINEX to enable high quality support and back-up. User can download this data and send it to Fugro's development centers for re-processing. Additional user defined output can be configured for automatic logging. Firmware can be upgraded using the web interface or using a USB stick at the front panel.

StarPack WEB Interface

StarPack
serial: 00072
 IP: 192.168.63.137
 base port: 40000

Logged in as: admin | [logout](#) | UTC: 17:22:13 19 Nov 2012

Status All Positions starfix_HP starfix_XP starfix_LI/EPlus starfix_G2 GNSS Best Position GNSS Heading Corrections COM I/O Predefined LAN I/O User LAN I/O MUX NTRIP Hardware Subscription NTP Configuration StarPack GNSS Cards Config Backups Maintenance Security FTP Web Interface QC Settings Quality Control All Positions Help StarPack Manual	<div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Starfix_HP 52° 05' 46.4969" N SD = 0.08m 4° 24' 21.7017" E SD = 0.22m + 58.10m SD = 0.09m Age :11s Resets :0 HP Stations PDOP :1.4 Locked :24m [521] [571] [580] [530] Satellites :10 F-test :0.3 </div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Starfix_XP 52° 05' 46.4962" N SD = 0.05m 4° 24' 21.6992" E SD = 0.08m + 58.12m SD = 0.06m Age :19s Resets :0 PDOP :1.4 Locked :25m Satellites :10 Clock & Orbit F-test :0.1 Corrections :[XP] </div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Starfix_EPlus 52° 05' 46.4591" N SD = 0.22m 4° 24' 21.6935" E SD = 0.21m + 59.32m SD = 0.40m Age :9s Resets :0 PDOP :1.2 Locked :25m Satellites :18 Clock & Orbit F-test :0.0 Corrections :[G2] </div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Starfix_G2 52° 05' 46.4977" N SD = 0.03m 4° 24' 21.7016" E SD = 0.03m + 58.13m SD = 0.05m Age :9s Resets :0 PDOP :1.2 Locked :25m Satellites :18 Clock & Orbit F-test :0.1 Corrections :[G2] </div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> GNSS 52° 05' 46.5091" N SD = 1.31m 4° 24' 21.6484" E SD = 0.97m + 60.82m SD = 2.34m PDOP :1.2 Satellites :18 </div> <div style="border: 1px solid #ccc; padding: 5px; margin-bottom: 5px;"> Best Position 52° 05' 46.4967" N SD = 0.02m 4° 24' 21.7009" E SD = 0.03m + 58.13m SD = 0.04m PDOP :1.2 Satellites :18 F-test :0.5 </div> <div style="border: 1px solid #ccc; padding: 5px;"> GNSS Heading 59.93° SD = 0.08° Distance O-C : 3.63m AEast : 3.14m Satellites : 12 ANorth : 1.82m Altitude : 0.00m </div>
---	---

Positioning and Heading solutions

The embedded processing software of the StarPack GNSS receiver provides multiple configurable simultaneous precise positioning solutions, including G2.

- Four independent correction sources
 - o Starfix.G2
 - o Starfix.XP
 - o Starfix.HP
 - o Starfix.L1
- Five solutions: Starfix.G2, Starfix.XP, Starfix.HP, Starfix.EPlus and Starfix.L1
- New “Best Position” solution, combining all available solutions in to one, using proper weighting. “Best Position” provides increased availability and better accuracy.
- A Heading solution between two GNSS antennae, in combination with a second GNSS card (in the same or another receiver).

StarPack applications

- Accurate height for tidal corrections and heave compensation
- Accurate position for seabed mapping surveys
- Accurate vertical reference for out of straightness pipeline surveys
- Accurate (instantaneous) heading source (in combination with a second GNSS card)
- Stable position for station keeping on DP vessels
- Accurate relative positioning of structures
- Automated vessel guidance

NTP support

The StarPack contains an NTP (Network Time Protocol) server, providing a time accuracy of 500 μ s or better with a convergence time after power-on within several minutes.

NTRIP client

The StarPack contains also NTRIP (Networked Transport of RTCM via Internet Protocol) client. When internet connection is available StarPack can be connected to Fugro’s (or third-party) corrections servers providing additional, independent from L-Band, corrections backup.

Quality control

Extensive quality control is provided through StarPackQC, a stand alone PC based application, or on web interface, Quality control parameters indicating precision, reliability and availability can be visualized for estimated positions as well as for corrections and individual satellites.

Technical specifications

GNSS hardware engine	<ul style="list-style-type: none"> • Trimble BD982 with two antenna inputs: 220 channel GPS/GLONASS, Galileo/BeiDou available with software option upgrade • Single or dual NovAtel OEMV-3: 72 channel GPS/GLONASS board • Trimble BD960: 72 channel GPS/GLONASS board (no longer manufactured, but serviceable)
Corrections	Integrated receiver for Starfix differential and orbit/clock corrections
Processor	Intel Pentium III, embedded Linux operating system
Data rate	1 Hz - 5Hz
Data storage	10 days, raw and correction data (1 Hz) on internal disk
Size	245 x 60 x 195 mm (W x H x D)
Weight	2 kg
Input voltage	80 – 250 VAC, 40 – 60 Hz
Input/output	4 RS232 ports, LAN with more than 30 configurable ports, 1 PPS
Operating temperature	-20°C – +50°C
Storage temperature	-40°C – +85°C
Humidity	95% non-condensing
Compliant	EMC 2004/108/EC (EN60945:2002) 2011/65/EU(RoHS 2)

Service/solution	Accuracy (hor. 95%)	System	Correction data	Coverage
Starfix.G2	0.1m	GPS GLONASS	Clock and orbit corrections	Global
Starfix.XP	0.1m	GPS	Clock and orbit corrections	Global
Starfix.HP	0.1m	GPS	Ionosphere-free carrier phase corrections from multiple reference stations	Regional <1000km*
Starfix.EPlus	1m	GPS GLONASS	Clock and orbit corrections	Global
Starfix.L1	1.5m	GPS	L1 pseudo range corrections from multiple reference stations	Regional <500km*
Best Position	0.1m	GPS GLONASS	All available correction data	Global
Heading	Better than 0.1° for baselines longer than 3m	GPS GLONASS	-	Global

* distance to reference station